

24730

## Wind-up stand »3000«

### Product variant

24730-000-55 - black

### Data

Base diameter	1,550 mm
EAN	4016842117062
Gewicht	12.33 kg
Height	from 1,405 to 3,000 mm
Height adjustment	hand crank with push-button system and locking screw
Leg construction	tube legs with double cross braces
Material	aluminum
Max. load capacity*	40 kg
Number of legs	3
Quality level	Starline
Rod combination	3-piece folding design
Size when folded	1,390 x 200 x 165 mm
Special features	steel extension tubes; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Type	black



Professional light and speaker stand with an innovative dual crank mechanism. A low base height of 1,405 mm ensures easy, ergonomic positioning of the load. The 3-piece tube combination reaches a height of 3 meters. Lifting and lowering the load is user-friendly, safe and reliable via two separate crank gears. The integrated »Auto Lock« system prevents sudden lowering of the load by automatic locking. The crank can also be removed to prevent unauthorised use. Since no cables are needed, the stand is completely maintenance-free. The robust stand focuses on stability and steadiness, so that the 5° stability test according to DIN 56950-3 with a load capacity of 40 kg is easily realised. The compact transport dimensions are 1,390 x 200 x 165 mm and the weight is approx. 12.0 kg. The integrated M10 threaded bush allows additional trusses or individual spotlights to be mounted directly.