

27500

XLR Microphone stand with gooseneck

Product variant

27500-000-55 - black

Data

| | |
|---------------------------------|--|
| Base diameter | 440 mm |
| EAN | 4016842121847 |
| Female connector for microphone | 3-pin XLR connector |
| Gewicht | 3.3 kg |
| Gooseneck diameter | 15 mm |
| Gooseneck length | 350 mm |
| Height | 1,520 mm |
| Leg construction | socket with foldable legs |
| Material | steel |
| Quality level | Starline |
| Special features | stand with wired XLR connections and additional gooseneck; angle plug 3-pin XLR connector; full-metal feet with sound-insulation rubber end caps provide excellent stability |
| Type | black |



Professional stand with wired XLR connections and additional gooseneck. This premium stand allows the microphone to be connected directly to the stand without a microphone clamp or external cable. There is an angle plug 3-pin XLR connector at the lower end of the tube for cable connection. High-quality digital audio cables are built into both the microphone stand and the gooseneck. These are drawn in, soldered and tested by hand at the KLOTZ AIS factory in Germany. The powder-coated stand has a height of 1,165 mm and can be extended to 1,520 mm with the included gooseneck. The robust, short full metal feet with impact sound absorbing foot caps ensure an excellent, space-saving positioning and are simply folded away for transportation.