

21467

Speaker stand »Ring Lock«

Product variant

21467-000-55 - black

Technical Data

Visibility

Height adjustment	spring-loaded bolt and locking screw
Tube end(s)	»Ring Lock« diameter 35 to 37 mm
Rod combination	2-piece folding design
Size when folded	1,160 mm
Leg construction	tube legs with double cross braces
Quality level	
Height	from 1,370 to 2,170 mm
Base diameter	1.320 mm
Number of legs	3
Max. load capacity*	50 kg
Type	black

* With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)

Special features further development of 214/6;
lightweight stand;
steel extension tube;
patented expanding mandrel system »Ring Lock«;
vibration-free connection due to moveable plastic splints

Price display

Material aluminum



An exceptional aluminum speaker stand with a unique patented expanding mandrel system that provides a stable, tight and firm fit for speakers. The movable plastic splints provide for a vibration-free connection between the rod and the speaker. Connecting the speaker is easy and is done using the handy ring lock - which is simply placed in position and screwed on. The height is adjusted by an easy-to-use spring-loaded bolt and locking screw. Double foot struts, zinc die cast clamping brackets and large end caps provide for highest degree of stand stability. It can't get any better than this!