

24730

Wind-up stand »3000«

Product variant

24730-000-55 - black

Technical Data

Max. load capacity*	40 kg
Height adjustment	hand crank with push-button system and locking screw
Visibility	
Rod combination	3-piece folding design
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Leg construction	tube legs with double cross braces
Quality level	
Number of legs	3
Type	black
Base diameter	1.550 mm
*	With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)
Height	from 1,405 to 3,000 mm
Price display	
Material	aluminum
Size when folded	1,390 x 200 x 165 mm
Special features	steel extension tubes; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts



Professional light and speaker stand with an innovative dual crank mechanism. A low base height of 1,405 mm ensures easy, ergonomic positioning of the load. The 3-piece tube combination reaches a height of 3 meters. Lifting and lowering the load is user-friendly, safe and reliable via two separate crank gears. The integrated »Auto Lock« system prevents sudden lowering of the load by automatic locking. The crank can also be removed to prevent unauthorised use. Since no cables are needed, the stand is completely maintenance-free. The robust stand focuses on stability and steadiness, so that the 5° stability test according to DIN 56950-3 with a load capacity of 40 kg is easily realised. The compact transport dimensions are 1,390 x 200 x 165 mm and the weight is approx. 12.0 kg. The integrated M10 threaded bush allows additional trusses or individual spotlights to be mounted directly.