

24740

Wind-up stand »4000«

Product variant

24740-000-55 - black

Technical Data

Max. load capacity*	40 kg
Height adjustment	hand crank with push-button system and locking screw
Visibility	
Rod combination	3-piece folding design
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Leg construction	tube legs with double cross braces
Quality level	
Number of legs	3
Type	black
*	With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)
Height	from 1,715 to 4,000 mm
Price display	
Material	aluminum
Size when folded	1,695 x 200 x 165 mm
Base diameter	2.000 mm
Special features	steel extension tubes; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts



Professional light and speaker stand with an innovative dual crank mechanism. The 3-piece tube combination covers a range of use from 1,715 to 4,000 mm height. The load is raised and lowered in a user-friendly, safe and reliable way via two separate crank gears. The integrated »Auto Lock« system prevents sudden lowering of the load by automatic locking. The crank can also be removed to prevent unauthorised use. Since no cables are used, the stand is completely maintenance-free. The focus of this robust stand is above all on stability and steadiness, so that a load capacity of 40 kg is easily realised. The compact transport dimensions are 1,695 x 200 x 165 mm and the weight is around 14.2 kg. The integrated M10 threaded bush can be used to mount additional crossbars or individual spotlights directly.