

24650

Lighting/Speaker stand

Product variant

24650-000-55 - black

Technical Data

Visibility	
Max. load capacity*	20 kg
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Rod combination	2-piece folding design
Special features	includes two height-adjustable feet for exceptional stability on uneven surfaces; integrated shock absorber; gradual height adjustment system
Height	from 1,420 to 2,420 mm
Type	black
Height adjustment	locking screw and safety hook
*	With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)
Price display	
Leg construction	flat steel plate
Quality level	
Base dimensions	489 x 489 mm
Material	steel



Attractive stand for lights and speaker cabinets. Thanks to the heavy, flat steel plate, the stand is suitable for use where space is at a premium. A carrying handle, a cable management and four sturdy feet are further useful features. Two of the feet are also height-adjustable, allowing continuous compensation for uneven floor surfaces of up to 3.5 mm. This ensures exceptional stability and a perfectly wobble-free setup at all times. The height is fixed with a safety hook and secured with a low-noise, backlash-free clamping screw. The slim design of the clamp enables space-saving transportation and ensures a stylish appearance. The usable height is between 1,420 and 2,420 mm and can be reached in 5 steps of 200 mm. The integrated M10 threaded bush enables the attachment of a crossbar or the direct attachment of lights. The maximum load capacity when fully extended is 20 kg.