

24651

Lighting/Speaker stand »Pro«

Product variant

24651-000-76 - pure white

Technical Data

Visibility

Type black

Special features knurled screw is impossible to lose;
silent and smooth height adjustment;
stable, lightweight round steel base with
plastic cover;
circumferential rubber profile reduces
undesirable vibration and footfall noise

Price display

Material rod combination made from aluminum,
handle bar zinc die-cast

Quality level

Height from 1,055 to 1,735 mm

Rod combination 2-piece folding design

Tube end(s) kfs.Ø 35 mm, Gewindebolzen M20

Height adjustment »Soft-Touch« one-hand clutch

Base dimensions 900 x 500 mm

Leg construction round base

Max. load capacity* 30 kg

* kfs.Bei zentrischer Belastung, auf
waagerechter Fläche und ohne Seitenkräfte
(Wind, Stöße etc.)



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (550 x 550 mm), the stand is ideal for use where space is at a premium. A carrying handle, a cable management system and four stable feet are further useful features. The usable height is between 1,420 and 2,420 mm and can be reached in 5 steps of 200 mm. The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum load capacity with full extension is 30 kg.