

24651

Lighting/Speaker stand »Pro«

Product variant

24651-000-76 - pure white

Technical Data

Visibility

Height adjustment	spring-loaded bolt and locking screw
Tube end(s)	diameter 35 mm, integrated threaded bush M10 for crossbars
Rod combination	2-piece folding design
Type	pure white
Special features	includes two height-adjustable feet for exceptional stability on uneven surfaces; integrated shock absorber; gradual height adjustment system

Quality level

Height	from 1,420 to 2,420 mm
Max. load capacity*	30 kg
*	With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)

Price display

Leg construction	flat steel plate
Material	steel
Base dimensions	550 x 550 mm



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (550 x 550 mm), the stand is ideal for use where space is at a premium. A carrying handle, a cable management system and four stable feet are further useful features. Two of the feet are also height-adjustable, allowing continuous compensation for uneven floor surfaces of up to 3.5 mm. This ensures exceptional stability and a perfectly wobble-free setup at all times. The usable height is between 1,420 and 2,420 mm and can be reached in 5 steps of 200 mm. The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum load capacity with full extension is 30 kg.