

26727

## Speaker stand »Pro«

### Product variant

26727-000-55 - black

### Technical Data

#### Visibility

**Height adjustment** spring-loaded bolt and locking screw

**Special features** includes two height-adjustable feet for exceptional stability on uneven surfaces; integrated shock absorber; mounting aid included; gradual height adjustment system: depending on the requirements, there are three ways to position the distance rod

**Rod combination** 2-piece folding design

#### Quality level

**Max. load capacity\*** 50 kg

**Type** black

\* With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)

#### Price display

**Leg construction** flat steel plate

**Material** steel

**Height** from 1,110 to 1,810 mm

**Tube end(s)** diameter 35 mm

**Base dimensions** 550 x 550 mm



Our strongest speaker stand with space-saving base plate. Thanks to the heavy, flat steel plate (550 x 550 mm), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. Two of the feet are also height-adjustable, allowing continuous compensation for uneven floor surfaces of up to 3.5 mm. This ensures exceptional stability and a perfectly wobble-free setup at all times. The usable height is between 1,110 and 1,810 mm and can be reached in 4 steps of 175 mm. The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The maximum centric load capacity with full extension is 50 kg.