24651

Lighting/Speaker stand »Pro«

Product variant

24651-000-55 - black



Technical Data

*	With centric loading, on a horizontal surface and without lateral forces (wind, shocks etc.)
Base dimensions	21.65 x 21.65"
EAN	4016842122523
Height	from 55.91 to 95.28"
Height adjustment	spring-loaded bolt and locking screw
Leg construction	flat steel plate
Material	steel
Max. load capacity*	66.139 lbs
Quality level	
Rod combination	2-piece folding design
Special features	includes two height-adjustable feet for exceptional stability on uneven surfaces; integrated shock absorber; gradual height adjustment system
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Type	black
Weight	17.31 kg

Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (21.653 x 21.653"), the stand is ideal for use where space is at a premium. A carrying handle, a cable management system and four stable feet are further useful features. Two of the feet are also height-adjustable, allowing continuous compensation for uneven floor surfaces of up to 0.118". This ensures exceptional stability and a perfectly wobble-free setup at all times. The usable height is between 55.905 and 95.275" and can be reached in 5 steps of 200 mm. The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum load capacity with full extension is 66.138 lbs.