

24654 Lighting/Speaker stand »Pro«

Product variant

24654-000-55 - black

Technical Data

Visibility

Height adjustment spring-loaded bolt and locking screw

Tube end(s) diameter 1.378", integrated threaded bush
M10 for crossbars

Rod combination 2-piece folding design

Quality level

Height from 55.91 to 95.28"

Special features includes two height-adjustable feet for
exceptional stability on uneven surfaces;
integrated shock absorber;
gradual height adjustment system:
depending on the requirements, there are
three ways to position the distance rod

Max. load capacity* 66.139 lbs

Type black

***** With centric loading, on a horizontal surface
and without lateral forces (wind, shocks etc.)

Price display

Leg construction flat steel plate

Material steel

Base dimensions 21.65 x 21.65"



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (21.653 x 21.653"), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. Two of the feet are also height-adjustable, allowing continuous compensation for uneven floor surfaces of up to 0.118". This ensures exceptional stability and a perfectly wobble-free setup at all times. The usable height is between 55.905 and 95.275" and can be reached in 5 steps of 7.874". The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum centric load capacity with full extension is 66.138 lbs.