

21351

Distance rod

Product variant

US-21351-000-55 - black

Data

Gewicht 4.85 lb: Height from 33.43 to 54.21 Height adjustment locking screw and safety hool Material stee Max. load capacity 77.162 lb: Rod combination 2-piece folding design Special features for precise and vertical fi		
Height from 33.43 to 54.21 Height adjustment locking screw and safety hool Material stee Max. load capacity 77.162 lbs Rod combination 2-piece folding design Special features for precise and vertical fill Tube end(s) diameter 1.378", threaded bolt M26	EAN	4016842122912
Height adjustment locking screw and safety hool Material stee Max. load capacity 77.162 lb: Rod combination 2-piece folding design Special features for precise and vertical fi Tube end(s) diameter 1.378", threaded bolt M20	Gewicht	4.85 lbs
Material stee Max. load capacity 77.162 lb: Rod combination 2-piece folding design Special features for precise and vertical fi Tube end(s) diameter 1.378", threaded bolt M20	Height	from 33.43 to 54.21"
Max. load capacity 77.162 lbs Rod combination 2-piece folding design Special features for precise and vertical fi Tube end(s) diameter 1.378", threaded bolt M26	Height adjustment	locking screw and safety hook
Rod combination 2-piece folding design Special features for precise and vertical fi Tube end(s) diameter 1.378", threaded bolt M20	Material	steel
Special features for precise and vertical fit Tube end(s) diameter 1.378", threaded bolt M20	Max. load capacity	77.162 lbs
Tube end(s) diameter 1.378", threaded bolt M20	Rod combination	2-piece folding design
	Special features	for precise and vertical fit
Type blace	Tube end(s)	diameter 1.378", threaded bolt M20
	Туре	black

Steel rod combination for use in subwoofers with M20 connection. The height is fixed with a safety hook and secured with a low-noise, backlash-free clamping screw. The slim design of the clamp enables space-saving transportation and ensures a stylish appearance. The usable height is between 33.425 and 54.212" and is achieved in 4 steps of 5.196". A plastic cap protects the speaker from scratching.



Telefax: +49 (0) 9342-806-150

E-Mail: contact(at)k-m.de