

24615

Lighting/Speaker stand

Product variant

US-24615-000-55 - black

Data

Base diameter	61.02"
EAN	4016842117055
Gewicht	17.813 lbs
Height	from 69.09 to 118.11"
Height adjustment	hand crank with push-button system and locking screw
Leg construction	tube legs with double cross braces
Material	aluminum
Max. load capacity*	77.162 lbs
Number of legs	3
Quality level	Starline
Rod combination	2-piece folding design
Size when folded	68.23 x 7.95 x 5.91"
Special features	steel extension tube; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Туре	black



High-quality aluminium light stand for professional use. The height adjustment from 69.094 to 118.11" is comfortable and safe thanks to a crank mechanism with »AutoLock« locking system. The ergonomic operation proves to be simple and user-friendly. The robust stand is focused on stability and steadiness, so that the 5° stability test according to DIN 56950-3 with a load capacity of 77.093 lbs is easily achieved. The compact transport dimensions are 68.228 x 5.906 x 7.953" and the weight is approx. 17.621 lbs. The integrated M10 threaded bush can be used to directly mount additional trusses or individual spotlights.

