

## 24653 Lighting/Speaker stand

### Product variant

US-24653-000-55 - black

### Data

Base dimensions	19.25 x 19.25"
EAN	4016842122035
Height	from 55.12 to 94.49"
Height adjustment	locking screw and safety hook
Leg construction	flat steel plate
Material	steel
Max. load capacity*	44.092 lbs
Product Category	Topline
Rod combination	2-piece folding design
Special features	integrated shock absorber; gradual height adjustment system; depending on the requirements, there are three ways to position the distance rod
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Type	black
Weight	31.746 lbs



Attractive stand for lights and smaller speaker cabinets. Thanks to the heavy, flat steel plate, the stand is suitable for use where space is at a premium. Depending on requirements, there are three ways to position the distance rod. In addition to the centered and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management and four sturdy feet are further useful features. The height is fixed with a safety hook and secured with a low-noise, backlash-free clamping screw. The slim design of the clamp enables space-saving transportation and ensures a stylish appearance. The usable height is between 55.118 and 94.488" and can be reached in 5 steps of 7.874". The integrated M10 threaded bush enables the attachment of a crossbar or the direct attachment of lights. The maximum load capacity with centric loading in the middle position is 44.092 lbs.