

24654

Lighting/Speaker stand »Pro«

Product variant

US-24654-000-76 - pure white

Data

| Data | |
|---------------------|--|
| Base dimensions | 21.65 x 21.65" |
| EAN | 4016842122738 |
| Gewicht | 38.36 lbs |
| Height | from 55.91 to 95.28" |
| Height adjustment | spring-loaded bolt and locking screw |
| Leg construction | flat steel plate |
| Material | steel |
| Max. load capacity* | 66.139 lbs |
| Quality level | Starline |
| Rod combination | 2-piece folding design |
| Special features | integrated shock absorber; gradual height adjustment system: depending on the requirements, there are three ways to position the distance rod |
| Tube end(s) | diameter 1.378", integrated threaded bush M10 for crossbars |
| Туре | pure white |



Attractive stand for lights and loudspeaker cabinets. Thanks to the heavy, flat steel plate (21.653 x 21.653"), the stand is ideal for use where space is at a premium. Depending on requirements, there are three ways to position the pole. In addition to the centric and off-center position, the tube combination can also be mounted in the corner. A carrying handle, a cable management system and four stable feet are further useful features. The usable height is between 55.905 and 95.275" and can be reached in 5 steps of 7.874". The tried and tested K&M clamping screw and the robust locking bolt are used for fixing. The integrated M10 threaded bush enables the attachment of a truss or the direct attachment of lights. The maximum centric load capacity with full extension is 66.138 lbs.

