

24740

Wind-up stand »4000«

Product variant

US-24740-000-55 - black

Data

Base diameter	78.74"
EAN	4016842117079
Gewicht	32.033 lbs
Height	from 67.52 to 157.48"
Height adjustment	hand crank with push-button system and locking screw
Leg construction	tube legs with double cross braces
Material	aluminum
Max. load capacity*	88.185 lbs
Number of legs	3
Quality level	Starline
Rod combination	3-piece folding design
Size when folded	66.73 x 7.87 x 6.50"
Special features	steel extension tubes; push-button system and hand crank avoid uncontrolled reverse motion; locking screw provides additional safety; zinc die-cast connecting parts
Tube end(s)	diameter 1.378", integrated threaded bush M10 for crossbars
Туре	black



Professional light and speaker stand with an innovative dual crank mechanism. The 3-piece tube combination covers a range of use from 67.52 to 157.48" height. The load is raised and lowered in a user-friendly, safe and reliable way via two separate crank gears. The integrated »AutoLock« system prevents sudden lowering of the load by automatic locking. The crank can also be removed to prevent unauthorised use. Since no cables are used, the stand is completely maintenance-free. The focus of this robust stand is above all on stability and steadiness, so that a load capacity of 88.106 lbs is easily realised. The compact transport dimensions are 66.732 x 7.874 x 6.496" and the weight is around 31.278 lbs. The integrated M10 threaded bush can be used to mount additional crossbars or individual spotlights directly.

